

## Date of compilation: 2021-06-16 Version: 1

## SECTION 1: IDENTIFICATION

0101		
1.1	Product identifier:	VEHICLE A/C CLEANER
	Other means of identification	on:
	Non-applicable	
1.2	Recommended use of the c	hemical and restrictions on use:
	Relevant uses: Cleaner	
	Uses advised against: All uses	not specified in this section or in section 7.3
1.3	Initial supplier identifier:	
	AUTOLAND Sp. Jawna J.Kisiele Oqrodowa 37	wski & JMoranski
	00-873 Warszawa - Poland	
	Phone.: 0048-32-47 22 531	
	autoland_hse@autoland.pl http://autoland.pl	
1.4	Emergency phone number:	

# SECTION 2: HAZARD IDENTIFICATION

#### 2.1 Classification of the substance or mixture:

### WHMIS 2015:

Classification of this product has been carried out in accordance with Part 2 of Hazardous Products Regulations (SOR/2015-17)

Aerosol 1: Flammable aerosols, Category 1, H222 Eye Irrit. 2: Eye irritation, Category 2, H319 Press. Gas: Pressure Gases, H280 **Label elements:** 

## 2.2 Label elements: WHMIS 2015:

#### WIIIII 20

Danger



### Hazard statements:

Aerosol 1: H222 - Extremely flammable aerosol.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Press. Gas: H280 - Contains gas under pressure; may explode if heated.

## **Precautionary statements:**

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P501: Dispose of contents and / or their container according to the separated collection system used in your municipality.

2.3 Health and physical hazards not otherwise classified (HHNOC - PHNOC):

Non-applicable

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

# 3.1 Substances:

- Non-applicable
- 3.2 Mixtures:

Chemical description: Aerosol

**Components:** 

In accordance with Schedule I of the Hazardous Products Regulations (SOR/2015-17), the product contains:

- CONTINUED ON NEXT PAGE -



## Date of compilation: 2021-06-16 Version: 1

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

64-17-5	ethanol	30 - <60 %
106-97-8	Butane	30 - <60 %
74-98-6	Propane	10 - <30 %
67-63-0	propan-2-ol	5 - <10 %
	106-97-8 74-98-6	106-97-8 Butane   74-98-6 Propane

## Other information:

Identification	Specific concentration limit	
ethanol CAS: 64-17-5	% (w/w) >=50: Eye Irrit. 2 - H319	

## SECTION 4: FIRST-AID MEASURES

## 4.1 Description of necessary measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

## By inhalation:

This product is not classified as hazardous through inhalation,however, it is recommended in case of intoxication symptoms to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

### By skin contact:

In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of modifications on the skin (stinging, redness, rashes, blisters,...), seek medical advice with this Safety data Sheet

## By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

#### By ingestion/aspiration:

In case of consumption, seek immediate medical assistance showing the SDS of this product.

## 4.2 Most important symptoms/effects, acute and delayed:

# Acute and delayed effects are indicated in sections 2 and 11.

### 4.3 Indication of immediate medical attention and special treatment needed, if necessary:

Non-applicable

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1 Suitable (and unsuitable) extinguishing media:

#### Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2).

#### Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

## 5.2 Specific hazards arising from the chemical:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

### 5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)



Date of compilation: 2021-06-16 Version: 1

# SECTION 5: FIRE-FIGHTING MEASURES (continued)

## Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

#### 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

## 6.3 Methods and materials for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### 6.4 Reference to other sections:

See sections 8 and 13.

# SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

### 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 0 °C

Maximum Temp.: 50 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

## 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters:



# Date of compilation: 2021-06-16 Version: 1

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

## Substances whose occupational exposure limits have to be monitored in the workplace:

#### British Columbia - Occupational Health and Safety Regulation section 5.48:

Identification Occupational exposure limits		
ethanol	TLV-TWA	
CAS: 64-17-5	TLV-STEL	
Butane	TLV-TWA	
CAS: 106-97-8	TLV-STEL	1000 ppm
propan-2-ol	TLV-TWA	200 ppm
CAS: 67-63-0	TLV-STEL	400 ppm

#### ALBERTA - Occupational Health and Safety Code:

Identification Occupational exposure limit		nits	
ethanol	8-hour	1000 ppm	1880 mg/m <sup>3</sup>
CAS: 64-17-5	15-minute		
Butane	8-hour	1000 ppm	
CAS: 106-97-8	15-minute		
Propane	8-hour	1000 ppm	
CAS: 74-98-6	15-minute		
propan-2-ol	8-hour	200 ppm	492 mg/m <sup>3</sup>
CAS: 67-63-0	15-minute	400 ppm	984 mg/m <sup>3</sup>

#### 8.2 Appropriate engineering controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

### B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Non-applicable

D.- Ocular and facial protection

Non-applicable

E.- Bodily protection

Non-applicable

F.- Additional emergency measures

It is not necessary to take additional emergency measures.

#### Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds (VOC) according to Canadian Environmental Protection Act, 1999:

Volatile organic compounds:92.37 % weightV.O.C. density at 20 °C:Non-applicable

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

**Appearance:** 

### Physical state at 20 °C:

Aerosol

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



Date of compilation: 2021-06-16 Version: 1

SECT	TON 9: PHYSICAL AND CHEMICAL PROPERTIES	S (continued)
	Appearance:	Fluid
	Color:	Colourless
	Odor:	Pleasant
	Odour threshold:	Non-applicable *
	Volatility:	
	Boiling point at atmospheric pressure:	-42 - 365 °C (Propellant)
	Vapour pressure at 20 °C:	Non-applicable *
	Vapour pressure at 50 °C:	<300000 Pa (300 kPa)
	Evaporation rate at 20 °C:	Non-applicable *
	Product description:	
	Density at 20 °C:	Non-applicable *
	Relative density at 20 °C:	Non-applicable *
	Dynamic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 40 °C:	Non-applicable *
	Concentration:	Non-applicable *
	pH:	Non-applicable *
	Vapour density at 20 °C:	Non-applicable *
	Partition coefficient n-octanol/water 20 °C:	Non-applicable *
	Solubility in water at 20 °C:	
	Solubility properties:	Non-applicable *
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Recipient pressure:	Non-applicable *
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Flammability:	
	Flash Point:	-104 °C (Propellant)
	Heat of combustion:	Non-applicable *
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	410 °C (Propellant)
	Lower flammability limit:	Non-applicable *
	Upper flammability limit:	Non-applicable *
	Explosive:	
	Lower explosive limit:	Non-applicable *
	Upper explosive limit:	Non-applicable *
9.2	Other information:	
	Surface tension at 20 °C:	Non-applicable *
	Refraction index:	Non-applicable *
	*Not relevant due to the nature of the product, not providing infor	mation property of its hazards.

# SECTION 10: STABILITY AND REACTIVITY

# 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.



Date of compilation: 2021-06-16 Version: 1

## SECTION 10: STABILITY AND REACTIVITY (continued)

#### 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

## 10.4 Conditions to avoid:

#### Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity		
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable		
Incompatible materials:						

### 10.5

Avoid strong acids Not applicable Avoid direct impact Not applicable Avoid	Avoid alkalis or strong bases

## 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions. complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

# SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A- Indestion (acute effect):

Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.

- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
  - Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for skin contact. For more information see section 3.
  - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
    - IARC: propan-2-ol (3); ethanol (1); d-limonene (3)
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
  - Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:



Date of compilation: 2021-06-16 Version: 1

## SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

#### Other information:

Non-applicable

### Specific toxicology information on the substances:

Identification Acute toxicity		e toxicity	Genus	
propan-2-ol	LD50 oral	5280 mg/kg	Rat	
CAS: 67-63-0	LD50 dermal	12800 mg/kg	Rat	
	LC50 inhalation	72.6 mg/L (4 h)	Rat	
ethanol	LD50 oral	6200 mg/kg	Rat	
CAS: 64-17-5	LD50 dermal	20000 mg/kg	Rabbit	
	LC50 inhalation	124.7 mg/L (4 h)	Rat	
Propane	LD50 oral	>5000 mg/kg		
CAS: 74-98-6	LD50 dermal	>5000 mg/kg		
	LC50 inhalation	>5 mg/L (4 h)		
Butane	LD50 oral	>5000 mg/kg		
CAS: 106-97-8	LD50 dermal	>5000 mg/kg		
	LC50 inhalation	658 mg/L (4 h)	Rat	

# SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

## 12.1 Ecotoxicity (aquatic and terrestrial, where available):

Identification		Acute toxicity	Species	Genus
ethanol	LC50	11000 mg/L (96 h)	Alburnus alburnus	Fish
CAS: 64-17-5	EC50	9268 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1450 mg/L (192 h)	Microcystis aeruginosa	Algae
propan-2-ol	LC50	9640 mg/L (96 h)	Pimephales promelas	Fish
CAS: 67-63-0	EC50	13299 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae

### 12.2 Persistence and degradability:

Identification	De	gradability	Biodegradability	
ethanol	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 64-17-5	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	89 %
propan-2-ol	BOD5	1.19 g O2/g	Concentration	100 mg/L
CAS: 67-63-0	COD	2.23 g O2/g	Period	14 days
	BOD5/COD	0.53	% Biodegradable	86 %

## 12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
ethanol	BCF	3
CAS: 64-17-5	Pow Log	-0.31
	Potential	Low



## Date of compilation: 2021-06-16 Version: 1

# SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	В	Bioaccumulation potential		
Butane	BCF	33		
CAS: 106-97-8	Pow Log	2.89		
	Potential	Moderate		
Propane	BCF	13		
CAS: 74-98-6	Pow Log	2.86		
	Potential	Low		
propan-2-ol	BCF	3		
CAS: 67-63-0	Pow Log	0.05		
	Potential	Low		

## 12.4 Mobility in soil:

Identification	Absorp	Absorption/desorption		Volatility	
ethanol	Кос	1	Henry	4.61E-1 Pa·m <sup>3</sup> /mol	
CAS: 64-17-5	Conclusion	Very High	Dry soil	Yes	
	Surface tension	2.339E-2 N/m (25 °C)	Moist soil	Yes	
Butane	Кос	900	Henry	96258.75 Pa·m <sup>3</sup> /mol	
CAS: 106-97-8	Conclusion	Low	Dry soil	Yes	
	Surface tension	1.187E-2 N/m (25 °C)	Moist soil	Yes	
Propane	Кос	460	Henry	71636.78 Pa·m <sup>3</sup> /mol	
CAS: 74-98-6	Conclusion	Moderate	Dry soil	Yes	
	Surface tension	7.02E-3 N/m (25 °C)	Moist soil	Yes	
propan-2-ol	Кос	1.5	Henry	8.207E-1 Pa·m <sup>3</sup> /mol	
CAS: 67-63-0	Conclusion	Very High	Dry soil	Yes	
	Surface tension	2.24E-2 N/m (25 °C)	Moist soil	Yes	

# 12.5 Results of PBT and vPvB assessment:

Non-applicable

## **12.6** Other adverse effects:

Not described

## SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1 Disposal methods:

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations. In case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See epigraph 6.2.

## Regulations related to waste management:

Legislation related to waste management:

Canadian Environmental Protection Act, 1999

# SECTION 14: TRANSPORT INFORMATION

## Transport of dangerous goods by land:

With regard to Transportation of Dangerous Goods Regulations including Amendment SOR/2017-100



Date of compilation: 2021-06-1	.6	Version: 1				
SECTION 14: TRANSPORT INFORMATION (continued)						
<b>A</b>			1011050			
		UN number:	UN1950			
	14.2	United Nations proper shipping name:	AEROSOLS, flammable			
	L4.3	Transport hazard class(es):	2			
2		Labels:	2.1			
▼ 1	L <b>4.4</b>	Packing group:	N/A			
1	L4.5	Environmental hazard:	No			
1	L <b>4.6</b>	Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises				
		Physico-Chemical properties:	see section 9			
1	14.7	Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):	Non-applicable			
Transport of dang	jerou	s goods by sea:				
With regard to IMDG 39-18:						
1	L <b>4.1</b>	UN number:	UN1950			
1	L <b>4.2</b>	United Nations proper shipping name:	AEROSOLS, flammable			
	L4.3	Transport hazard class(es):	2			
		Labels:	2.1			
	L <b>4.4</b>	Packing group:	N/A			
1	L4.5	Marine pollutant:	No			
1	L <b>4.6</b>		ser needs to be aware of, or needs to comply with, in			
		_	conveyance either within or outside their premises			
		Special regulations:	63, 959, 190, 277, 327, 344			
		EmS Codes:	F-D, S-U			
		Physico-Chemical properties:	see section 9			
		Limited quantities:	1L Nev eveligeble			
		Segregation group:	Non-applicable			
1	L4.7	Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):	Non-applicable			
Transport of dangerous goods by air:						
With regard to IATA/ICAO 2021:						
1	L <b>4.1</b>	UN number:	UN1950			
	L <b>4.2</b>	United Nations proper shipping name:	AEROSOLS, flammable			
	L4.3	Transport hazard class(es):	2			
2		Labels:	2.1			
1	L <b>4.4</b>	Packing group:	N/A			
1	L4.5	Environmental hazard:	No			
1	L <b>4.6</b>	Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises				
		Physico-Chemical properties:	see section 9			
1	14.7	Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):	Non-applicable			
L						

# SECTION 15: REGULATORY INFORMATION

**15.1** Safety, health and environmental regulations specific for the product in question:

Domestic Substances List (DSL): ethanol ; Butane ; Propane ; propan-2-ol Non-Domestic Substances List (NDSL): Non-applicable **Specific provisions in terms of protecting people or the environment:** 



Date of compilation: 2021-06-16 Version: 1

# SECTION 15: REGULATORY INFORMATION (continued)

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

#### Other legislation:

Canadian Environmental Protection Act, 1999

## SECTION 16: OTHER INFORMATION

## Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Part 4 and Schedule I of the Hazardous Products Regulations (SOR/2015-17)

## Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation.

H280: Contains gas under pressure; may explode if heated.

H222: Extremely flammable aerosol.

## Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

## Principal bibliographical sources:

http://whmis.org/

### Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5-day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 CL50: Lethal Concentration 50 EC50: Effective concentration 50 Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.